


Tuya RFID One-Door Access Control Systems



H3-BT

Tuya RFID One-Door Access Control Systems

The H3-BT is a Bluetooth-enabled waterproof touch keypad + RFID access controller. It's integrated with Tuya which supports 100 users (including 255 card/PIN users).

It's available for both iOS and Android.

Specifications

User Capacity	Hardware User: 1000, APP User: 100	Relay	One (NO, NC, Common)
Common User	988	Adjustable Relay Output Time	0-99 Seconds
Visitor User	10	Lock Output Load	2 Amp Maximum
Panic User	2	Wiegand Interface	EM card version: Wiegand 26~44 bits input & output (Factory default: Wiegand 26bits)
PIN Length	4~6 digits		Mifare card version: Wiegand 26~44 bits, 56bits, 58bits input & output (Factory default: Wiegand 34bits)
Operating Voltage	12~18V DC		
Idle Current	<= 60mA	PIN Output	4 bits, 8bits (ASCII), 10 digits Virtual
Active Current	<=150mA		Number (Factory default: 4bits)
Proximity Card Reader	EM or Mifare	Environment	Meets IP66
Radio Technology	125KHz/13.56MHz	Operating Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Read Range	2~6cm	Operating Humidity	0%RH ~ 98%RH
Wiring Connections	Relay output, exit button, alarm, door contact, Wiegand input/output	Physical	Zinc-Alloy
		Color	Sliver & Black
		Dimensions	L148 x W43.5 x H22 (mm)

